

# Examples for the qTable function

Enrico Schumann

es@enricoschumann.net

We attach the package and create some random data.


```
> require("NMOF")
> x <- rnorm(100L, mean = 0, sd = 1.5)
> y <- rnorm(100L, mean = 1, sd = 1)
> z <- rnorm(100L, mean = 1, sd = 0.5)
> X <- cbind(x, y, z)
> summary(X)
```

	x		y		z
Min.	:-3.668	Min.	:-1.591	Min.	:-0.168
1st Qu.:	-1.303	1st Qu.:	0.177	1st Qu.:	0.723
Median	:-0.189	Median	: 0.964	Median	: 1.008
[ reached getOption("max.print") -- omitted 3 rows ]					

A call to qTable could like this, and it will result in the  $\LaTeX$  output below.

```
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
             circlesize = 0.0125, xmin = -10, xmax = 10, dec = 2))
```


	median	min	max	
x	-0.19	-3.67	4.76	— • —
y	0.96	-1.59	3.81	— • —
z	1.01	-0.17	2.39	— • —




If you use Sweave, use `<<results=tex>>=` to start a code chunk.

## Examples


```
> ## with limits
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
             circlesize = 0.0125, xmin = -10, xmax = 10, dec = 2))
```




```
> ## without specified limits
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
             circlesize = 0.0125, dec = 2))
```




```
> ## 3 digits
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
             circlesize = 0.0125, dec = 3))
```




```
> ## specific labels, but no limits
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
             labels = c(-8,2,8), at = c(-8,2,8),
             circlesize = 0.0125, dec = 1))
```




```
> ## specific labels and limits, linethickness
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
             labels = c("a","b","c"), at = c(-8,2,8),
             circlesize = 0.02, dec = 1, linethickness = "0.2ex",
             xmin = -10, xmax = 10))
```



```
> ## specific labels and limits, linethickness
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
  labels = c("a","b","c"), at = c(-8,2,8),
  circlesize = 0.02, dec = 1, linethickness = "0.2ex",
  xmin = -10, xmax = 10))
```



```
> ## with limits and alternative functions
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
  circlesize = 0.0125, xmin = -10, xmax = 10, dec = 2,
  funs = list(average = mean,
    `10th Q.` = function(x) quantile(x, 0.1),
    `90th Q.` = function(x) quantile(x, 0.9))))
```



```
> ## with limits and without summary stats
> cat(qTable(X, yoffset = -0.025, unitlength = "5cm",
  circlesize = 0.0125, xmin = -10, xmax = 10, dec = 2,
  funs = list()))
```

