

# Package ‘mupet’

May 9, 2026

**Title** Multiclass Performance Evaluation Toolkit

**Version** 0.1.0

**Description** Implementation of custom 'tidymodels' metrics for multi-class prediction models with a single negative class. Currently are implemented macro-average sensitivity and specificity as in Mortaz, Ebrahim (2020) "Imbalance accuracy metric for model selection in multi-class imbalance classification problems" <[doi:10.1016/j.knosys.2020.106490](https://doi.org/10.1016/j.knosys.2020.106490)> and a generalized weighted Youden index as in Li, D.L., Shen F., Yin Y., Peng J.X and Chen P.Y. (2013) "Weighted Youden index and its two-independent-sample comparison based on weighted sensitivity and specificity" <[doi:10.3760/cma.j.issn.0366-6999.20123102](https://doi.org/10.3760/cma.j.issn.0366-6999.20123102)>.

**License** MIT + file LICENSE

**Suggests** testthat (>= 3.0.0)

**Config/testthat/edition** 3

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**URL** <https://github.com/astamm/mupet>, <https://astamm.github.io/mupet/>

**BugReports** <https://github.com/astamm/mupet/issues>

**Imports** rlang, yardstick

**NeedsCompilation** no

**Author** Lise Bellanger [aut],  
Manon Simonot [aut],  
Aymeric Stamm [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-8725-3654>>)

**Maintainer** Aymeric Stamm <[aymeric.stamm@cnr.fr](mailto:aymeric.stamm@cnr.fr)>

**Repository** CRAN

**Date/Publication** 2026-01-21 20:10:09 UTC

## Contents

macro_average_sensitivity	2
macro_average_specificity	3
weighted_youden_index	4

<b>Index</b>	<b>7</b>
--------------	----------

---

macro\_average\_sensitivity  
*Macro Average Sensitivity*

---

### Description

This function computes the macro-average sensitivity for a multi-class prediction model. It assumes that the *negative* class is the first one.

### Usage

```
macro_average_sensitivity_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = "first",
  ...
)

macro_average_sensitivity(data, ...)

## S3 method for class 'data.frame'
macro_average_sensitivity(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = "first",
  ...
)
```

### Arguments

truth	The column identifier for the true class results (that is a factor).
estimate	The column identifier for the predicted class results (that is also factor).

estimator	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary".
...	Currently unused.
data	Either a data.frame containing the columns specified by the truth and estimate arguments, or a table/matrix where the true class results should be in the columns of the table.

**Value**

A scalar storing the value of the macro-average sensitivity score.

**Examples**

```
fold1 <- subset(yardstick::hpc_cv, Resample == "Fold01")
macro_average_sensitivity_vec(fold1$obs, fold1$pred)
macro_average_sensitivity(fold1, obs, pred)
```

---

macro\_average\_specificity

*Macro Average Specificity*

---

**Description**

This function computes the macro-average specificity for a multi-class prediction model. It assumes that the *negative* class is the first one.

**Usage**

```
macro_average_specificity_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = "first",
  ...
)

macro_average_specificity(data, ...)
```

```
## S3 method for class 'data.frame'
macro_average_specificity(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = "first",
  ...
)
```

### Arguments

truth	The column identifier for the true class results (that is a factor).
estimate	The column identifier for the predicted class results (that is also factor).
estimator	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary".
...	Currently unused.
data	Either a data.frame containing the columns specified by the truth and estimate arguments, or a table/matrix where the true class results should be in the columns of the table.

### Value

A scalar storing the value of the macro-average specificity score.

### Examples

```
fold1 <- subset(yardstick::hpc_cv, Resample == "Fold01")
macro_average_specificity_vec(fold1$obs, fold1$pred)
macro_average_specificity(fold1, obs, pred)
```

---

weighted\_youden\_index *Weighted Youden Index*

---

### Description

This function computes the weighted Youden index for a multi-class prediction model. It assumes that the *negative* class is the first one.

**Usage**

```

weighted_youden_index_vec(
  truth,
  estimate,
  sensitivity_weight = 0.5,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = "first",
  ...
)

weighted_youden_index(data, ...)

## S3 method for class 'data.frame'
weighted_youden_index(
  data,
  truth,
  estimate,
  sensitivity_weight = 0.5,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = "first",
  ...
)

```

**Arguments**

<code>truth</code>	The column identifier for the true class results (that is a factor).
<code>estimate</code>	The column identifier for the predicted class results (that is also factor).
<code>sensitivity_weight</code>	A scalar value specifying the weight to put on sensitivity. Defaults to 0.5 which puts equal weights to sensitivity and specificity.
<code>estimator</code>	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights.
<code>event_level</code>	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> .
<code>...</code>	Currently unused.
<code>data</code>	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a table/matrix where the true class results should be in the columns of the table.

**Value**

A scalar storing the value of the weighted Youden index.

**Examples**

```
fold1 <- subset(yardstick::hpc_cv, Resample == "Fold01")
weighted_youden_index_vec(fold1$obs, fold1$pred)
weighted_youden_index(fold1, obs, pred)
```

# Index

macro\_average\_sensitivity, [2](#)  
macro\_average\_sensitivity\_vec  
    (macro\_average\_sensitivity), [2](#)  
macro\_average\_specificity, [3](#)  
macro\_average\_specificity\_vec  
    (macro\_average\_specificity), [3](#)  
  
weighted\_youden\_index, [4](#)  
weighted\_youden\_index\_vec  
    (weighted\_youden\_index), [4](#)